

# FITT Refittex Premium

## 介绍，优势，以及接合测试



用于输送加压的食品级液体，果汁和酒精度数打50度的饮料的软管。高强度聚酯增强软质PVC软管



- ★★★★★ 裁剪方便
- ★★★★★ 低温状态下依旧保持柔软（低至-5°C）
- ★★★★★ 表面透明
- ★★★★★ 抗裂抗硬化

-20°C/+60°C 工作温度

英寸 Ø Inside	内径 Ø Internal	外径 Ø External	壁厚 Thickness	使用压力 Working Pressure	弯曲半径 Bending Radius	长度 Length	每卷重量 Weight/ Roll
inc	mm	mm	mm	Mpa	mm	m	kg/roll
-	4	9	2.5	1.5	15	100	7
-	6	11	2.5	1.5	20	100	9
5/16	8	13.5	2.75	1.5	35	100	12
-	9	15	3	1.5	45	100	15
3/8	10	16	3	1.2	45	100	16
-	12	18	3	1.2	55	100	18
-	15	22	3.5	1.0	80	100	26
3/4	19	26	3.5	1.0	95	50	16
-	21.5	29	3.75	1.0	120	50	19
1	25	33	4	1.0	140	50	24
-	32	41	4.5	0.7	185	50	35
1 1/2	38	48	5	0.6	300	50	45
-	45	56	5.5	0.6	400	40	48
-	50	62	6	0.6	440	40	54
-	63	80	8.5	0.4	650	20	53
-	75	92	8.5	0.3	800	20	62

工作 / 爆破压力为常温23°C时的数值