


fit lightflex



软管适用于抽吸输送空气、灰尘、锯末和刨花。PVC螺旋软管采用硬质抗震PVC螺旋加强。

Hose for suction and air passage, dust, sawdust and shavings. PVC spiral hose equipped with reinforcement spiral in rigid shock-resistant PVC.



- 柔性 - Flexibility
- 内壁光滑度 - Smooth internal surface
- 15°C/+60°C 工作温度 - Working temperature



英寸 Inches	内径 Ø internal	外径 Ø external	壁厚 Thickness	工作压力 Working pressure	爆破压力 Bursting pressure	负压 Vacuum	弯曲半径 Bending radius	长度 Length	每米重量 Weight per meter
inc	mm	mm	mm	bar	bar	mH ₂ O	mm	m	g/m
3/4	19	23,80	2,4	-	-	3	19	50	110
1	25	30,00	2,5	-	-	3	25	50	140
-	30	35,40	2,7	-	-	3	30	50	200
1 1/4	32	37,40	2,7	-	-	3	32	50	220
-	35	40,60	2,8	-	-	3	35	50	240
1 1/2	38	44,20	3,1	-	-	3	38	50	270
-	40	46,40	3,2	-	-	3	40	50	280
1 3/4	45	51,40	3,2	-	-	3	45	50	360
2	50	57,20	3,6	-	-	3	50	50	450
-	60	68,40	4,2	-	-	2	60	50	540
2 1/2	63	71,40	4,2	-	-	2	63	50	565
-	70	78,40	4,2	-	-	2	70	50	640
3	76	84,60	4,3	-	-	2	76	50	690
-	80	89,40	4,7	-	-	2	80	50	780
-	90	99,40	4,7	-	-	2	90	50	900
4	100	109,60	4,8	-	-	2	100	30	990
-	110	119,60	4,8	-	-	1	110	30	1160
-	120	130,00	5,0	-	-	1	120	30	1200
-	125	135,20	5,1	-	-	1	125	30	1310
-	130	140,60	5,3	-	-	1	130	30	1400
-	140	151,00	5,5	-	-	1	140	30	1550
-	150	161,60	5,8	-	-	1	150	30	1670
-	160	172,60	6,3	-	-	1	160	20	1950
-	180	193	6,5	-	-	1	180	20	2250
-	203	216,4	6,7	-	-	1	203	20	2600

工作 / 爆破压力为常温23°C时的数值
Working and Bursting pressure at 23°C

软管内径的大小以及对应的公差范围根据UNI EN ISO 1307:2008标准进行设定和控制。长度公差为±5%
Inner diameters and corresponding tolerances according to the norm UNI EN ISO 1307:2008. The length tolerance is ± 5%