

fitt refittex gas en 16436



燃气输送软管，根据EN 16436标准，适用于家用电器、炉子、燃气灯和户外取暖器。PVC三层软管，聚酯线编织加强。

Gas delivery hose ideal for domestic appliances, stoves, gas lamps and outdoor radiators according to EN 16436. Flexible PVC hose with high strength polyester textile reinforcement.

- 柔韧性 - Flexibility
- 内壁光滑度 - Smooth internal surface
- 抗紫外线 - UV resistance
- 30°C/+70°C 工作温度 - Working temperature



英寸 Inches	内径 Ø internal	外径 Ø external	壁厚 Thickness	工作压力 Working pressure	爆破压力 Bursting pressure	负压 Vacuum	弯曲半径 Bending radius	长度 Length	每米重量 Weight per meter
inc	mm	mm	mm	bar	bar	mH ₂ O	mm	m	g/m
-	4	11,0	3,5	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	200	105
-	5	12,0	3,5	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	100	123
-	6,3	13,30	3,5	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	100	134
-	8	15,0	3,5	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	50	164
-	9	16,0	3,5	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	50	176
-	10	20,0	5,0	as prescribed by EN 16436 class2	as prescribed by EN 16436 class2	-	-	30	307

工作 / 爆破压力为常温23°C时的数值
Working and Bursting pressure at 23°C



DVGW认证符合德国指令DIN EN 16436-1。
DVGW certification in compliance with the German directive DIN EN 16436-1.