

fit refittex pu 20 bär



软管适用于喷涂枪、空压机、气笔及其他一般气动工具。适合配套压缩空气卷管器在机械车间内使用。100%PU三层软管，聚酯线编织加强。

Hose usable with spray guns, compressed air, airbrushes, pneumatic tools in general, ideal for automatic winders for compressed air, commonly used in mechanical workshops. 100% polyurethane hose with polyester reinforcement.

- 耐磨损 - Abrasion resistance
- 柔韧性 - Flexibility
- 内壁光滑度 - Smooth internal surface
- 耐臭氧 - Ozone resistance
- 30°C/+75°C 工作温度 - Working temperature



英寸 Inches	内径 Ø internal	外径 Ø external	壁厚 Thickness	工作压力 Working pressure	爆破压力 Bursting pressure	负压 Vacuum	弯曲半径 Bending radius	长度 Length	每米重量 Weight per meter
inc	mm	mm	mm	bar	bar	mH ₂ O	mm	m	g/m
1/4	6	10	2	20	60	-	-	100	60
5/16	8	12	2	20	60	-	-	100	77
3/8	10	14,50	2,25	20	60	-	-	100	102
1/2	13	19	3	20	60	-	-	100	178

工作 / 爆破压力为常温23°C时的数值
Working and Bursting pressure at 23°C