



适用于输送下水管废水的软管。即使在低温环境下，该螺旋软管依然质地柔软、抗挤压。它采用了经过验证可吸收异味的特殊弹性材料，没有金属螺旋，便于切割和快速安装。

专利申请中。

*Ideal hose for the passage of waste water in the drains. Extremely flexible anti-crushing spiral hose even at low temperatures. Made with tested odour-absorbing special elastomers, with no metal spiral for easy cutting and quick fitting.*

Patent pending.

抗挤压 - Crush resistance

柔韧性 - Flexibility

内壁光滑度 - Smooth internal surface

低温柔韧性 - Cold flexibility

工作温度 - Working temperature

-40°C/+65°C



英寸 Inches	内径 $\varnothing$ internal	外径 $\varnothing$ external	壁厚 Thickness	工作压力 Working pressure	爆破压力 Bursting pressure	负压 Vacuum	弯曲半径 Bending radius	长度 Length
inc	mm	mm	mm	bar	bar	mH <sub>2</sub> O	mm	m
3/4"	20	29.4	4.7	3	9	9	45	20
1"	25	34.6	4.8	3	9	9	70	20
1 1/2"	38	50	6.0	2.8	8.4	9	130	20
2"	50	62.6	6.3	2.5	7.5	9	200	20

工作 / 爆破压力为常温23°C时的数值

Working and Bursting pressure at 23°C



无气味



不含金属



低温柔韧性