

FITT Refitrex 20 Bar



软管用于输送压缩空气、水、杀菌剂溶液，农药和化肥。适合连接空压机使用，工作压力 20 bar/290 psi。
PVC三层软管，聚酯线编织加强。

Hoses are used to deliver compressed air, water, fungicide solutions, pesticides and fertilizers. Suitable for use with air compressors, working pressure 20 bar/290 psi.
PVC three-layer hose, reinforced with polyester braid.

- 柔性 - Flexibility
- 内壁光滑度 - Smooth internal surface
- 20°C/+60°C 工作温度 - Working temperature



英寸 Inches	内径 Ø internal	外径 Ø external	壁厚 Thickness	工作压力 Working pressure	爆破压力 Bursting pressure	负压 Vacuum	弯曲半径 Bending radius	长度 Length	每米重量 Weight per meter
inc	mm	mm	mm	bar	bar	mH ₂ O	mm	m	g/m
1/4	6	11	2,5	20	60	-	-	50	87
5/16	8	13	2,5	20	60	-	-	25	104
5/16	8	13	2,5	20	60	-	-	50	104
5/16	8	13	2,5	20	60	-	-	100	104
3/8	10	15	2,5	20	60	-	-	25	125
3/8	10	15	2,5	20	60	-	-	50	125
3/8	10	15	2,5	20	60	-	-	100	125
1/2	13	19	3,0	20	60	-	-	25	190
1/2	13	19	3,0	20	60	-	-	50	190
1/2	13	19	3,0	20	60	-	-	100	190
5/8	16	23	3,5	20	60	-	-	50	270
3/4	19	26	3,5	20	60	-	-	50	312
1	25	33	4,0	20	60	-	-	50	460

工作 / 爆破压力为常温23°C时的数值
Working and Bursting pressure at 23°C